













# Model DP55



-  IP65 / IK10
-  Type 1/ NACS
-  55" LCD Screen
-  Autitheft Design
-  ISO15118-2 (optional)
-  Restart Button
-  OCPP1.6 J/OCPP2.0.1 Upgradeable
-  RFID (ISO/IEC14443 A/B)
-  Three Layers Casing Design
-  LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional

Model Name	DP55/48A*2	DP55/80A*2
<b>Power Specification</b>		
Input AC Rating	208-240Vac	
Input Max.AC Current	48A * 2	80A * 2
Frequency	60Hz	
Max.Output Power	11.5kW * 2	19.2kW * 2
<b>User Interface &amp; Control</b>		
Display	55" LCD Screen	
LED Indicator	Yes	
Push Buttons	Restart Button	
User Authentication	RFID (ISO/IEC14443 A/B), APP	
<b>Communication</b>		
Network Interface	LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional	
Communication Protoco	OCPP1.6 J/OCPP2.0.1 Upgradeable	
Cummunication Function	ISO/IEC 15118 Optional	
<b>Environmental</b>		
Operation Temperature	-22°F~122°F	
Humidity	5%~95% RH, Non-condensing	
Altitude	≤6562ft(2000m), No Derating	
<b>Mechanical</b>		
IP/IK Level	NEMA Type3R(IP65)/IK10	
Cabinet Dimension (W×D×H)	50.28"×8.27"×72.01"(1277mm×210mm×1829mm)	
Weight	99.21lbs(45kgs)	
Cable & Plug	Type 1 or NACS 18ft(5.5m)(Standard)/25ft(7.5m)(Optional)	
<b>Protection</b>		
Multiple Protection	OVP(Over Voltage Protection), OCP(Over Current Protection), OTP(Over Temperature Protection), UVP(Under Voltage Protection), SPD(Surge Protection Detection), Grounding Protection, SCP(Short Circuit Protection),- Control Pilot Fault, Relay Welding Detection, CCID Self-test	
<b>Regulation</b>		
Safety	UL 2594, UL2231-1/-2	
Certif icate	ETL, FCC	
Charging Interface	SAE J1772 Type 1/ NACS	

