




# Model LP-CP308D



 IP55 / IK10


 Type 2 Socket


 7" Touch Screen

 ISO5118-2

 OCPP1.6 J/OCPP2.0.1 Upgradeable

 RFID (ISO/IEC14443 A/B)

 3-layer housing for easy maintenance

 LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional

Model Name		LP-CP308D
<b>Power Specification</b>		
Input AC Rating	400Vac±10%	
Input Max.AC Current	32A * 2	
Frequency	50/60Hz	
Max.Output Power	22kW * 2	
<b>User Interface &amp; Control</b>		
Display	7" Touch Screen	
LED Indicator	Yes	
User Authentication	RFID (ISO/IEC14443 A/B), APP	
<b>Communication</b>		
Network Interface	LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional	
Communication Protocol	OCPP1.6 J/OCPP2.0.1 Upgradeable	
<b>Environmental</b>		
Operation Temperature	-30°C~50°C	
Humidity	5%~95% RH, Non-condensing	
Altitude	≤ 2000m, No Derating	
<b>Mechanical</b>		
IP/IK Level	IP55 / IK10	
Charging Pile Dimensions (W×D×H)	400mm×200mm×1370mm	
Base Dimensions (W×D×H)	450mm×290mm×40mm	
Weight	40kgs	
<b>Protection</b>		
Multiple Protection	OVP(Over Voltage Protection), OCP(Over Current Protection), OTP(Over Temperature Protection), UVP(Under Voltage Protection), SPD(Surge Protection Detection), Grounding Protection, SCP(Short Circuit Protection), Control Pilot Fault, Relay Welding Detection, RCD(DC 6mA)	
<b>Regulation</b>		
Safety	IEC 61851-1, IEC 61851-21-2	
Certificate is in processing	CE, CB, UKCA	
Charging Interface	IEC 62196-2 Complaint, Type 2 Socket	