














Model CS308



-  IP66 / IK10
-  Integration App NACS/SAEJ 1772 Plug
-  7" LCD Screen
-  OCPP1.6 J/OCPP2.0.1 Upgradeable
-  Antitheft Design
-  RFID (ISO/IEC14443 A/B)
-  ISO15118-20 (optional)
-  Three Layers Casing Design
-  Up to 80A(19.2kW)
-  LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional
-  Restart Button

Model Name	CS308-A32	CS308-A40	CS308-A48	CS308-A80
Power Specification				
Input AC Rating	208-240Vac			
Input Max.AC Current	32A	40A	48A	80A
Frequency	60Hz			
Max.Output Power	7.6kW	9.6kW	11.5kW	19.2kW
User Interface & Control				
Display	7" LCD Screen			
LED Indicator	Yes			
Push Buttons	Restart Button			
User Authentication	RFID (ISO/IEC14443 A/B), APP			
Communication				
Network Interface	LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional			
Communication Protoco	OCPP1.6 J/OCPP2.0.1 Upgradeable			
Cummunication Function	ISO/IEC 15118 Optional			
Environmental				
Operation Temperature	-22°F~122°F			
Humidity	5%~95% RH, Non-condensing			
Altitude	≤6562ft(2000m), No Derating			
Mechanical				
IP/IK Level	NEMA Type3R(IP66)/IK10			
Cabinet Dimension (W×D×H)	12.32" × 6.18" × 17.76"(313mm×157mm×451mm)			
Weight	16.98lbs(7.7kgs)			
Cable & Plug	Type 1 or NACS 18ft(5.5m)(Standard)/25ft(7.5m)(Optional)			
Protection				
Multiple Protection	OVP(Over Voltage Protection), OCP(Over Current Protection), OTP(Over Temperature Protection), UVP(Under Voltage Protection), SPD(Surge Protection Detection), Grounding Protection, SCP(Short Circuit Protection),- Control Pilot Fault, Relay Welding Detection, CCID Self-test			
Regulation				
Safety	UL 2594, UL2231-1/-2			
Certif icate	ETL, FCC			
Charging Interface	SAE J1772 Type 1/ NACS			

